



ACERO



ARCILLA



NUBE

BASIC CHARACTERISTICS:

Series name:	VENACIÓN
Size (cm.):	40x120
Colours:	ACERO, ARCILLA, NUBE
Range Quantity:	3
Type:	WALL TILE WHITE BODY
Family:	CONCRETA

TECHNICAL CHARACTERISTICS:

Fabrication process:	Single-fired porous white-body tile	
Absorption group (ISO 13006):	BIII	
Finish:	GL	
Rectified:	Yes	
Body:	White Body	
Surface Finish:	Matt	
Work size (mm):	400 x 1200 x 10,8	
Aesthetic classification and shade variations:	V.2	
Diferent design number:	11	
Facial dimension range and surface quality:	Complies with the standard	UNE EN ISO 10545-2

Certifications:



PHYSICAL CHARACTERISTICS:

Water absorption:	E>10%	UNE EN ISO 10545-3
Braking strength (S):	> 200N	UNE EN ISO 10545-4
Flexural tensile strength (N/mm2):	≥15 N/mm2	
Lineal thermal expansion between 20° to 100°C	< 9*10-6 / °C	UNE EN ISO 10545-8
Thermic shock resistance:	Complies with the standard	UNE EN ISO 10545-9
Crazing resistance:	Complies with the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	Not apply	UNE EN ISO 10545-12

CHEMICAL PROPERTIES:

Resistance to home cleaning products and swimming pool salts:	Clase A	UNE EN ISO 10545-13
Resistance to High concentration acids and bases:	Minimum HB	
Resistance to Low concentration acids and bases:	Minimum LB	
Resistance to staining:	Complies with the standard	UNE EN ISO 10545-14

CE MARKING:

	003CPR-A/11-4-2013
--	--------------------

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. Fábrica licenses products from Argenta Ceramica S.L. For more information about instalation and grouting visit the Argenta website: www.argentaceramica.com. The packing list of these pieces are indicated on the Argenta website: www.argentaceramica.com/packing-list . The stated weight is approximate, it may vary up to 5% depending on the model, the variation may be greater for products with relief. Documents with commercial information cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L. The color of the tile on this technical data sheet is for guidance only and may differ from the actual tile color.

Certifications:

